

CMCI N31-AIO-E-C9997-CAS by Camarb



VAI AL CANALE YOUTUBE
Watch us on youtube



SCOPRI DI PIÙ SUL NOSTRO SITO
Find out more on our website



CMCI N31-AIO-E-C997-CAS by Camarb

CARATTERISTICHE:

Macchina a colonna alta speciale (400 mm) ad un ago elettronica, con servo motore integrato, RASAFILO/AFFRANCATURA, doppio trasporto a rotanti sincronizzati per mezzo di motori passo passo. Crochet ad asse orizzontale per cuciture tipo driver e modelli con cuciture ad angolo sul tallone. Inoltre si caratterizza per essere "a pozzo" consentendo un utilizzo versatile anche come una normale macchina a colonna.

CAMPO D'IMPIEGO:

Il suo particolare sistema di trasporto punta d'ago permette la cucitura di materiali difficoltosi come gli imbottiti o di materiali a più strati evitando scorrimenti. Nella lavorazione di tomaie chiuse, la colonna destra permette di poter liberamente guidare la tomaia sul lato sinistro della colonna, peculiarità vantaggiosa per le tomaie da bambino. Il dispositivo rasafilo, l'affrancatura e l'alzapiedino rendono più efficiente il lavoro.

DATI TECNICI:

- Velocità cucitura: 2500 punti/min.
- Lunghezza punto max: 5 mm
- Filato max: 301
- Alzata piedino: 10 mm
- Sistema ago: 134-LR
- Voltaggio: 230 V 50/60 Hz
- Peso: 140 Kg
- Dimensioni imballo: 105x55x127 cm

FEATURES:

Special high column machine (400 mm), single needle, electronic, with integrated servo motor. THREAD TRIMMER / BACKTRACKING. Double transport rotating synchronized by means of stepper motors. Rotating Horizontal hook (for driver types shoes), angle shaped sewing on heel. Furthermore it is "well" shaped so that it can be used just like a normal post machine.

APPLICATION AREA:

It's special needle-moving system allows to sew difficult materials such as padded multi-layer materials, avoiding them from slipping. When sewing closed uppers, the right post-bed allows to move the upper on the left side of the post-bed, feature for child's uppers. The thread trimmer, the backtracking and the presser foot lifter make the working progress more efficient.

TECHNICAL DATA:

- Sewing speed: 2500 stitches/min.
- Max. stitch length: 5 mm
- Threads max.: 301
- Lifting presser foot: 10 mm
- Needle system: 134-LR
- Voltage: 230 V 50/60 Hz
- Weight: 140 Kg
- Packaging size: 105x55x127 cm

