

CMCI N31-AIO-E-C997-CP by Camarb



VAI AL CANALE YOUTUBE
Watch us on Youtube



SCOPRI DI PIÙ SUL NOSTRO SITO
Find out more on our website



CMCI N31-AIO-E-C997-CP by Camarb

CARATTERISTICHE:

Macchina a colonna elettronica con servo motore integrato nella testa di cucitura, ad 1 ago, trasporto a griffa rotante, piedino rotella sincronizzato con il movimento dell'ago per mezzo di motori passo. Dispositivo rasafilo, affrancatura elettrica e sollevamento del piedino elettrico. Crochet montato su albero orizzontale.

CAMPO D'IMPIEGO:

Il suo particolare sistema di trasporto punta d'ago permette la cucitura di materiali difficoltosi come gli imbottiti o di materiali a più strati evitando scorrimenti. Nella lavorazione di tomaie chiuse, la colonna destra permette di poter liberamente guidare la tomaia sul lato sinistro della colonna, peculiarità vantaggiosa per le tomaie da bambino. Il dispositivo rasafilo, l'affrancatura e l'alzapiedino rendono più efficiente il lavoro.

DATI TECNICI:

- Velocità cucitura max: 2800 punti/min. (mod A-b)
- Velocità cucitura max: 2400 punti/min (mod C)
- Lunghezza punto max: 4.5 mm
- Tipo di punto: 301
- Sistema ago: 134-LR
- Voltaggio: 230 V 50/60 Hz
- Peso: 100 Kg
- Dimensioni imballo: 105x55x127 cm

FEATURES:

Post-bed sewing machine with servo-drive integrated in the sewing head, single needle, rotary feed dog, synchronized needle and presser foot by means of stepper motors. Thread trimmer, electric backtracking and electric presser foot lift.

APPLICATION AREA:

It's needle-moving system allows to sew difficult materials such as padded items or multi-layer materials, avoiding them from slipping. When sewing closed uppers, the right post-bed allows to move the upper on the left side of the post-bed, advantageous features for child's uppers. The thread trimmer, the backtracking and the presser foot lifter make the working progress more efficient.

TECHNICAL DATA:

- Max sewing speed: 2800 stitches/min. (mod. A-B)
- Max sewing speed: 2400 stitches/min. (mod C)
- Max. stitch length: 4.5 mm
- Kind of stitch. : 301
- Needle system: 134-LR
- Voltage: 230 V 50/60 Hz
- Weight: 100 Kg
- Packaging size: 105x55x127 cm

